# ASCENTX



16-X1

#### CELLULAR TELEPHONE ENTRY SYSTEM WITH KEYPAD

#### **FEATURES**

- · 4G ITF cellular
- High-definition Ascent Camera for still photos
- Photo push notifications
- · 2 Wiegand inputs
- Ascent Link integration
- Control up to 2 gates/doors
- Cloud-based access control management
- Up to 10,000 app, text, and voice users
- Up to 1,000 keypad codes
- Rollover calling—up to 3 phone numbers
- Broadcast calling—up to 10 phone numbers
- Push and/or email event and status notifications

















powered by



GET THE SUMMIT CONTROL APP





#### VERSATILE AND CONVENIENT

Control your gate or door from anywhere using a computer, tablet, or phone.

#### AN ASCENT WITH A VIEW

Get visual ID for all guests with photo push notifications, and receive photos automatically or whenever you choose.

#### POWERFULLY EXPANDABLE

Network multiple Ascent units together and manage multiple entries via Summit Control.

#### GET CONNECTED EVERY TIME

Assign multiple phone numbers to be called in order or simultaneously upon call button press, ensuring a connection is always made.







#### **SPECIFICATIONS**

## PHYSICAL Dimensions 8.42"(H) x 7.45"(W) x 5.15"(D)

Shipping Weight 9 lbs.

**ELECTRICAL** 

Input 12–24 VAC/DC

12-VDC power supply included (PS-12DC1)

Current Draw less than 190 mA @ 12 VDC

less than 160 mA @ 24 VDC

with relay latched and backlit components on

**RELAY** 

Contact Rating 10 A @ 120 VAC / 24 VDC

Max Switching Voltage 250 VAC / 30 VDC

Max Switching Current 15 A

Max Switching Power 240 W / 2,770 VA

COMMUNICATION

Cellular Network 4G LTE


**ENVIRONMENTAL** 


Operating Temperature -15 to 158 °F

▲ Actual voltage should be no more than 10% beyond specified range. Use of the included 12-VDC power supply is recommended.

#### CONTROL IT YOUR WAY







### GET STARTED NOW!

#### PAY JUST ONE BILL!\*

Unit includes a GSM SIM card ready for activation.

We do ALL the legwork for you!



