EDGE E¹



27-210 SERIES

SMART KEYPADS

FEATURES

- Control up to 2 gates/doors
- 2 Wiegand inputs
- 2 event inputs
- 2 digital inputs
- · LED-backlit keypad
- Bluetooth connectivity
- · App-based programming and management
- SBI Flex™ 64-bit and standard 26-bit protocol

MODELS

- · 27-210 Edge E1 Smart Keypad
- 27-215 Edge E1 Smart Keypad + Intercom

Model 27-210 features a mount for a card reader (not included).





GET THE EDGE SMART KEYPAD APP





POWERFULLY SIMPLE APP

All programming and management can be done quickly and securely via the app.

SBI FLEX 64-BIT PROTOCOL

Our proprietary Wiegand protocol allows for 4- to 11-digit keypad codes with 3-digit facility code for maximum flexibility.

DUAL 365-DAY TIMERS

A separate 365-day timer on each relay gives you the versatility and control you need.

CONFIGURABLE USER PERMISSIONS

Set specific user permissions on all keypad codes, transmitters, card readers, and long-range tag readers independently.







SPECIFICATIONS

PHYSICAL

Dimensions 6.21"(H) x 7.44"(W) x 5.25"(D)

Shipping Weight 5 lbs.

ELECTRICAL

Input 12–24 VAC/DC

12-VDC power supply included (PS-12DC1)

Current Draw less than 111 mA @ 12 VDC

less than 60 mA @ 24 VDC

with one relay latched and LED components on

RELAY

Contact Rating 10 A @ 120 VAC / 24 VDC

COMMUNICATION


Connection Bluetooth

ENVIRONMENTAL

Operating Temperature -15 to 158 °F

▲ Actual voltage should be no more than 10% beyond specified range. Use of the included 12-VDC transformer is recommended.


CONTROL IT YOUR WAY



† Administrator only

CONNECTIVITY





Model 27-210 shown

AVAILABLE MODELS (SEE PRICE GUIDE TO SEE ALL MODELS)



EDGE E1
Keypad
27-210



EDGE E1 + INTERCOM
Keypad w/ Intercom
27-215