



27-230 SERIES

SMART KEYPAD AND CARD READER COMBOS

FEATURES

- Control up to 2 gates/doors
- 1 Wiegand input
- · 2 event inputs
- · 2 digital inputs
- · 3 proximity card reader options
- Bluetooth connectivity
- · App-based programming and management
- SBI Flex™ 64-bit and standard 26-bit protocol

MODELS

- · 27-230 Edge E3 SecurePass Smart Keypad and Card Reader
- · 27-230HID Edge E3 HID Smart Keypad and Card Reader
- 27-230SK Edge E3 SK Smart Keypad and Card Reader





GET THE EDGE SMART KEYPAD APP





POWERFULLY SIMPLE APP

All programming and management can be done quickly and securely via the app.

SBI FLEX 64-BIT PROTOCOL

Our proprietary Wiegand protocol allows for 4- to 11-digit keypad codes with 3-digit facility code for maximum flexibility.

DUAL 365-DAY TIMERS

A separate 365-day timer on each relay gives you the versatility and control you need.

CONFIGURABLE USER PERMISSIONS

Set specific user permissions on all keypad codes, transmitters, card readers, and long-range tag readers independently.







SPECIFICATIONS

PHYSICAL

Dimensions $6.21"(H) \times 7.44"(W) \times 5.25"(D)$

Shipping Weight 5 lbs.

ELECTRICAL

Input 12–24 VAC/DC

12-VDC power supply included (PS-12DC1)

Current Draw less than 111 mA @ 12 VDC

less than 60 mA @ 24 VDC

with one relay latched and LED components on

RELAY

Contact Rating 10 A @ 120 VAC / 24 VDC

COMMUNICATION


Connection Bluetooth

ENVIRONMENTAL

Operating Temperature -15 to 158 °F


▲ Actual voltage should be no more than 10% beyond specified range. Use of the included 12-VDC transformer is recommended.


CONTROL IT YOUR WAY



† Administrator only

CONNECTIVITY





Model 27-230 shown

AVAILABLE MODELS



EDGE E3 SECUREPASS
Keypad & Card Reader (SecurePass)
27-230



EDGE E3 HID
Keypad & Card Reader (HID)
27-230HID



EDGE E3 SK
Keypad & Card Reader (Secura Key)
27-2305K