

# AdvantageDKE

Digital Keypad Economy



The AdvantageDKE line of digital keyless entry offers both post or single gang, surface mount configurations. All models are stand alone and have 100 fully programmable, four digit codes.

AdvantageDKE post mount models are housed in heavy metal, powder coated enclosures with stainless steel faceplates. A metal keypad is used providing years of trouble free use.

With a 100 code capacity, the 26-100L and the 26-100sg keypads are the perfect solution for many low cost installations.



# AdvantageDKE

## General Specifications



26-100L



26-100sg

- Input: 12-24 VAC or VDC
- Output: n/o or n/c contact 1-9 second
- Operating temperature: -15 to 175 Fahrenheit
- 16 gauge stainless steel faceplate
- 16 gauge powder coated enclosure
- Dimensions:
  - 26-100L: 5.25h x 4.00w x 3.00d
  - 26-100sg: 4.50h x 2.75w x 0.75d
- Ship weight: 5 lbs.

	DC Load	AC Load
Contact Rating	1A @ 24V	.5A @ 120V
Max. switching voltage	150V	220V
Max. carrying current	2A	2A
Max. switching power	28W	60VA

## Features

- Conformal coated circuitry for weather resistant performance
- 100 programmable four digit codes
- Programmable Personal Master Code
- Programmable Latch / Unlatch Code
- Night Light
- Variable relay output time: 1 – 9 seconds
- Audible tone
- Non-volatile memory
- Power consumption: 25mA @ 24VAC
- Limited two year warranty



**AMERICAN**  
**ACCESS SYSTEMS**

