RemotePro CR

Weigand Output Card Readers



American Access Systems now offers the **RemotePro CR** line of wiegand output card readers, available in post or surface mount. In addition, all surface mount models may be post mounted with the additional purchase of a mounting plate (#2-005 or 2-006).

Post mount **RemotePro CR** wiegand output card readers (#23-006 & 23-006i) feature a stainless steel faceplate in a heavy metal, powder coated enclosure with nightlight, with the card reader mounted to the faceplate. Each AAS **RemotePro CR** is constructed of very durable and vandal resistant Lexan, providing years of trouble free entry.

The **RemotePro CR** series is designed to operate in conjunction with the American Access Systems <u>AdvantageDG</u> card reader controller system, the AAS <u>ProAccess 200</u> multi door controller, as well as many popular security management systems using a wiegand protocol. Simply connect the **RemotePro CR** of your choice to a new or existing master controller (via 6 conductor, 22 guage wire) and you have immediate access control. This is a perfect solution for expanding an access control system that already utilizes an existing master controller.









RemotePro CR



23-006



23-006i



40-006



40-008



40-009



General Specifications

- Input: 9 12 VDC (supplied by master controller)
- Input: (#40-009 ONLY) 24VDC-2A sold separately
- Operating temperature: -15 to 175 Fahrenheit
- · Dimensions:

23-006: 6.625h x 5.50w x 4.25d 23-006i: 6.625h x 5.50w x 4.25d 40-006: 3.125h x 1.75w x 0.75d 40-008: 5.00h x 5.00w x 1.00d 40-009: 12.00h x 12.00w x 1.00d

- Intercom: 8 ohm Mylar speaker w/ call button
- Ship3weight:

23-006: 5 lbs. 23-006: 7 lbs. 40-006: 2 lbs. 40-008: 4 lbs. 40-009: 7 lbs.

Features

Read Range:

23-006: 0.5 – 2 inches 23-006i: 0.5 – 2 inches 40-006: up to 3 inches 40-008: up to 8 inches 40-009: up to 22 inches

- Audible tone (#40-008 & 40-009 only)
- · LED indicators
- Night Light (#23-006 & 23-006i only)
- Optional camera (#23-006 & 23-006i only)
- Optional vehicle tag:
 - 6 to 8 foot read range capability
 - functional with #40-009 reader ONLY
 - Attaches to windshield
 - AAS part # 40-012 ProxPass cards
- Limited one year warranty





