StandAlone Touchplate

Touch Plate Card Readers



The American Access Systems line of **StandAlone Touchplate** card readers combine the latest in touch plate technology with the ease of non PC programming.

Each post mount **StandAlone Touchplate** unit features a a high grade stainless steel faceplate with heavy metal, powder coated enclosure. Mounted in the face plate is a SecuraKey touch plate reader with the controller board safely mounted inside the enclosure. Also available is the surface mount model, constructed of durable Lexan for years of trouble free entry.

With two models of **StandAlone Touchplate** readers to choose from, AAS has the perfect unit for almost every situation. If a simple system with no audit trail, remote slave or PC programming is called for, then the 11-3500 is perfect. However, if more is required of the reader, then choose the 11-65000. With a 1000 transaction memory buffer that can be printed out on an RS-232 serial port printer (AAS #21-045 or #21-047), this unit will report time, date, card number entered, relay activated and valid / invalid card. The 11-65000 can also hook to a PC for programming and audit capabilities using SK-Net, a full featured Windows software.

In addition, this unit allows an additional "slave" touch plate reader (model # 11-000) to be wired to it, making it the ideal product for an entry / exit application or where two touch plate readers are needed.









StandAlone Touchplate



11-3500 11-65000 11-000 (slave)



11-3500s 11-65000s 11-000s (slave)

General Specifications

- Input: 12 16 VAC or VDC (12VAC transformer included)
- Output: n/o or n/c contact 1-30 second
- Operating temperature: -15 to 150 Fahrenheit
- · Dimensions:

Post Mount: 5.25h x 4.75w x 4.50d Surface mount: 4.60h x 4.00w x 2.25d

Ship weight: 5 lbs.

Features

- 3,500 card capacity
- · Programmable Latch / Unlatch Card
- Programmable Sleep Card
- Three strikes you're out
- Timed Anti Pass Back
- Non-volatile memory
- Night Light
- · Limited one year warranty

11-65000 & 11-65000s

- 65,000 card capacity
- 15 Time Zones / 32 Holidays
- 5,000 memory transaction buffer
- · Modem / Network capability
- PC Compatible w/ SK-NET software
- · Programmable Latch / Unlatch Card
- Programmable Sleep Card
- 500 Limited Use Cards
- 3 auxiliary inputs:
 - user defined (door monitor, bell, remote open, etc.)
- Automatic Daylight Savings Time
- · Timed Anti Pass Back
- Non-volatile memory
- Compatible with one "slave" unit #11-000
- · Limited one year warranty
- Night Light







