

CHARGERS



S-TC1A, S-TC36A

BATTERY TRICKLE CHARGERS

FEATURES

- Microprocessor-controlled
- LED indicators
- Overcharge protection
- Weather-resistant housing
- Ring terminal connections
- For use with 6 and 12-volt batteries*



* S-TC36A for use with 12-volt batteries only.

A SOLUTION FIT FOR YOU

From light-duty to robust, we have the charger for you, no matter the application.

NO MORE DEAD BATTERIES

Make dead batteries a thing of the past! Keep the batteries on everything from RVs to gate operators charged and ready to go.

RUGGED & DURABLE

With an IP65-rated, weather-resistant enclosure, our chargers are made to last!

INTELLIGENT CHARGING

By providing a charge only when needed, our chargers keep your battery charged safely with no risk of overcharge.

SPECIFICATIONS



S-TC1A

1-AMP TRICKLE CHARGER
(6 AND 12-VOLT BATTERIES)

PRODUCT

Dimensions 5.6"(L) x 2.3"(W) x 1.5"(H)
Shipping Weight 1 lb.

ELECTRICAL

Input 110-120 VAC
Output (selectable) 6 VDC or 12 VDC, 1 A
Charging Voltage 7.2 V ± .13 V
6-volt battery
14.4 V ± .25 V
12-volt battery
Efficiency >70%

ENVIRONMENTAL

Operating Temperature -4 to 122 °F



S-TC36A

3.6-AMP TRICKLE CHARGER
(12-VOLT BATTERIES)

PRODUCT

Dimensions 2.44"(H) x 2.44"(W) x 1.30"(D)
Shipping Weight 1.1 lbs.

ELECTRICAL

Input 110-120 VAC
Output 12 VDC, 3.6 A
Charging Voltage 14.4 V ± .25 V
Efficiency >75%

ENVIRONMENTAL

Operating Temperature -4 to 122 °F



SECURITY BRANDS INC™
your *partner* in access control

www.ShopAmericanAccess.com
(800) 878-7829